



Pitched tile roof mounting kit

Flexible, simple clean on different tile roofing




- Installation site: Pitched roof
- Roof cladding: Suitable for most types of cladding
- Roof Slope: Up to 45°
- Building height: Up to 20m
- Wind speed: Up to 88m/s(316.8kmh/196.9mph)
- Standard: AS/NZ1170.2:2011, JIS C 8955:2011, other international standards
- Supporting profile: Minimum two rails supporting each panel
- Distance between rail fixings: Depending on load condition, refer to manual
- PV module: Framed, unframed
- Module orientation: Landscape, portrait
- Size of module array: Any layout up to site condition
- Material: Anodized aluminum 6005 T5, stainless steel 304, 410
- Color: Natural, powder coated
- Module widths: Maximum 1.0m
- Module lengths: Maximum 2.0m
- Warranty: 10 years limited warranty, refer to warranty doc
- All profiles are available in various lengths or can be cut to measure.



Standard 3 panel tile kit

Each Standard 3 panel tile kit comprises of:

- **AT-CG-010** Rail 3200mm
Quantity:2 units



- **AT-H01** Tile roof hook
Quantity:6 units


Each Contains:		Quantity
AT-AU001	Stainless steel hook	1
AT-29	T module	1
M8*30	Stainless steel bolt	1
ST6.3*80	Self-tapping screw	3



Additional components for complete kit

- **AT-S10** Rail splice kit
Quantity*:1 unit

Each Contains:		Quantity
AT-S10	Splice	1
M8*20	Stainless steel bolt	2




- **AT-C09** Mid clamp kit
Quantity*:4 units

Each Contains:		Quantity
AT-FWNY-09	Mid T	1
M8*20	Stainless steel bolt	1
AT-29	T module	1



- **AT-C12** End clamp kit
Quantity*:4 units

Each Contains:		Quantity
AT-12	End Z	1
M8*50	Stainless steel bolt	1
AT-29	T module	1



*Depending on the site condition, the components quantity might change. Please refer to the manual.