



Product Service

CERTIFICATE

No. Z2 17 09 72092 241

Holder of Certificate: Shanghai JA Solar Technology Co., Ltd.No. 118, Lane 3111,
West Huancheng Road
Fengxian District
201401 Shanghai
PEOPLE'S REPUBLIC OF CHINA**Certification Mark:****Product:**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 704061604115-06

Valid until: 2022-09-03



Date, 2017-09-08

(Zhulin Zhang)

Page 1 of 4



Product Service

CERTIFICATE

No. Z2 17 09 72092 241

Model(s):

JAM6(K)-72-345/PR/1500V, JAM6(K)-72-350/PR/1500V, JAM6(K)-72-355/PR/1500V, JAM6(K)-72-360/PR/1500V, JAM6(K)-72-365/PR/1500V, JAM6(K)-60-285/PR/1500V, JAM6(K)-60-290/PR/1500V, JAM6(K)-60-295/PR/1500V, JAM6(K)-60-300/PR/1500V, JAM6(K)-72-320/4BB/1500V, JAM6(K)-72-325/4BB/1500V, JAM6(K)-72-330/4BB/1500V, JAM6(K)-72-335/4BB/1500V, JAM6(K)-72-340/4BB/1500V, JAM6(K)-60-265/4BB/1500V, JAM6(K)-60-270/4BB/1500V, JAM6(K)-60-275/4BB/1500V, JAM6(K)-60-280/4BB/1500V, JAM72S01-345/PR, JAM72S01-350/PR, JAM72S01-355/PR, JAM72S01-360/PR, JAM72S01-365/PR, JAM60S01-285/PR, JAM60S01-290/PR, JAM60S01-295/PR, JAM60S01-300/PR, JAM72S01-320/SC, JAM72S01-325/SC, JAM72S01-330/SC, JAM72S01-335/SC, JAM72S01-340/SC, JAM60S01-265/SC, JAM60S01-270/SC, JAM60S01-275/SC, JAM60S01-280/SC, JAM72D00-330/BP, JAM72D00-335/BP, JAM72D00-340/BP, JAM72D00-345/BP, JAM72D00-350/BP, JAM72D00-355/BP, JAM60D00-275/BP, JAM60D00-280/BP, JAM60D00-285/BP, JAM60D00-290/BP, JAM60D00-295/BP, JAM60D00-300/BP, JAM60D00-285/PR, JAM60D00-290/PR, JAM60D00-295/PR, JAM60D00-300/PR, JAM72D00-340/PR, JAM72D00-345/PR, JAM72D00-350/PR, JAM72D00-355/PR, JAM72D00-360/PR, JAM72S03-360/PR, JAM72S03-365/PR, JAM72S03-370/PR, JAM72S03-375/PR, JAM60S03-300/PR, JAM60S03-305/PR, JAM60S03-310/PR, JAM6(K)-72-345/PR, JAM6(K)-72-350/PR, JAM6(K)-72-355/PR, JAM6(K)-72-360/PR, JAM6(K)-72-365/PR, JAM6(K)-60-285/PR, JAM6(K)-60-290/PR, JAM6(K)-60-295/PR, JAM6(K)-60-300/PR, JAM6(K)-72-320/4BB, JAM6(K)-72-325/4BB, JAM6(K)-72-330/4BB, JAM6(K)-72-335/4BB, JAM6(K)-72-340/4BB, JAM6(K)-60-265/4BB, JAM6(K)-60-270/4BB, JAM6(K)-60-275/4BB, JAM6(K)-60-280/4BB.

Parameters:

Rated Output Power at STC:	See attachment.
Construction:	Framed or Frameless, with Junction box, Cable and Connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute; No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China
Safety Class:	Class II
Maximum System Voltage:	1500 V DC or 1000 V DC
Fire Safety Class:	Details refer to attachment Class C or Class A according to UL790

Tested according to:

IEC 61215-1(ed.1)
IEC 61215-1-1(ed.1)
IEC 61215-2(ed.1)
IEC 61730-1(ed.2)
IEC 61730-2(ed.2)

Production Facility(ies):

79395, 72092, 72056, 90968, 95903, 97323

Page 2 of 4

CERTIFICATE
No. Z2 17 09 72092 241



Product Service

The following models will be covered by above certificate:

System voltage:1500 V DC	
Model	Rated Output Power at STC
JAM6(K)-72-345/PR/1500V, JAM6(K)-72-350/PR/1500V, JAM6(K)-72-355/PR/1500V, JAM6(K)-72-360/PR/1500V, JAM6(K)-72-365/PR/1500V,	345 W, 350 W, 355 W, 360 W, 365 W,
JAM6(K)-60-285/PR/1500V, JAM6(K)-60-290/PR/1500V, JAM6(K)-60-295/PR/1500V, JAM6(K)-60-300/PR/1500V,	285 W, 290 W, 295 W, 300 W,
JAM6(K)-72-320/4BB/1500V, JAM6(K)-72-325/4BB/1500V, JAM6(K)-72-330/4BB/1500V, JAM6(K)-72-335/4BB/1500V, JAM6(K)-72-340/4BB/1500V,	320 W, 325 W, 330 W, 335 W, 340 W,
JAM6(K)-60-265/4BB/1500V, JAM6(K)-60-270/4BB/1500V, JAM6(K)-60-275/4BB/1500V, JAM6(K)-60-280/4BB/1500V,	265 W, 270 W, 275 W, 280 W,
JAM72D00-330/BP, JAM72D00-335/BP, JAM72D00-340/BP, JAM72D00-345/BP, JAM72D00-350/BP, JAM72D00-355/BP,	330 W, 335 W, 340 W, 345 W, 350 W, 355 W,
JAM60D00-275/BP, JAM60D00-280/BP, JAM60D00-285/BP, JAM60D00-290/BP, JAM60D00-295/BP, JAM60D00-300/BP,	275 W, 280 W, 285 W, 290 W, 295 W, 300 W,
JAM60D00-285/PR, JAM60D00-290/PR, JAM60D00-295/PR, JAM60D00-300/PR,	285 W, 290 W, 295 W, 300 W,
JAM72D00-340/PR, JAM72D00-345/PR, JAM72D00-350/PR, JAM72D00-355/PR, JAM72D00-360/PR,	340 W, 345 W, 350 W, 355 W, 360 W,

System voltage:1000 V DC	
Model	Rated Output Power at STC
JAM6(K)-72-345/PR, JAM6(K)-72-350/PR, JAM6(K)-72-355/PR, JAM6(K)-72-360/PR, JAM6(K)-72-365/PR,	345 W, 350 W, 355 W, 360 W, 365 W,
JAM6(K)-60-285/PR, JAM6(K)-60-290/PR, JAM6(K)-60-295/PR, JAM6(K)-60-300/PR,	285 W, 290 W, 295 W, 300 W,
JAM6(K)-72-320/4BB, JAM6(K)-72-325/4BB, JAM6(K)-72-330/4BB, JAM6(K)-72-335/4BB, JAM6(K)-72-340/4BB,	320 W, 325 W, 330 W, 335 W, 340 W,
JAM6(K)-60-265/4BB, JAM6(K)-60-270/4BB, JAM6(K)-60-275/4BB, JAM6(K)-60-280/4BB,	265 W, 270 W, 275 W, 280 W,

CERTIFICATE
No. Z2 17 09 72092 241



Product Service

System voltage: 1000 or 1500 V DC	
Model	Rated Output Power at STC
JAM72S01-320/SC, JAM72S01-325/SC, JAM72S01-330/SC, JAM72S01-335/SC, JAM72S01-340/SC,	320 W, 325 W, 330 W, 335 W, 340 W,
JAM60S01-265/SC, JAM60S01-270/SC, JAM60S01-275/SC, JAM60S01-280/SC,	265 W, 270 W, 275 W, 280 W,
JAM72S01-345/PR, JAM72S01-350/PR, JAM72S01-355/PR, JAM72S01-360/PR, JAM72S01-365/PR,	345 W, 350 W, 355 W, 360 W, 365 W,
JAM60S01-285/PR, JAM60S01-290/PR, JAM60S01-295/PR, JAM60S01-300/PR,	285 W, 290 W, 295 W, 300 W,
JAM72S03-360/PR, JAM72S03-365/PR, JAM72S03-370/PR, JAM72S03-375/PR,	360 W, 365 W, 370 W, 375 W,
JAM60S03-300/PR, JAM60S03-305/PR, JAM60S03-310/PR.	300 W, 305 W, 310 W.

John